For Internal Distribution Only

Alternating Gradient Synchrotron Department
BROOKHAVEN NATIONAL LABORATORY
Associated Universities, Inc.
Upton, New York 11973

EP&S Division Technical Note
No. 112

B5 Tunes for Experiment 766

Gerry M. Bunce

June 3, 1985

The following plots were made for a beam at the B-target which is (1.4 mm x1 mrad)$_x$. (1.3 mm x 2 mrad)$_y$. These are half sizes, taken from calculations for the switchyard; however, they appear to be consistent with the observed spot size on B. After the beam traverses the target, the multiple-scattering blow-up should be ± 2 mrad. The plots do not have this additional spread folded in. A $\Delta p/p$ of ± .3% was used and it is assumed the servo system holds the beam steady at B. These sizes are Transport half sizes, which nominally contain 90% of the beam.

Tune A — This is the "standard" tune where the upstream quads are set for B1 at 10 GeV/c. The "wavy hole" aperture (vertical) is shown as ± 1/2". This tune appears to give poor transmission, as is observed. Q6/7, however, are at opposite polarity from what is now used!

Tune B — The polarities of the upstream quads remain the same and the beam is squeezed through the apertures.

Tune C — The upstream quad polarities are interchanged. The transmission should be quite high.

Tune D — Again, the upstream quad polarities have been inverted, but with their settings chosen to get optimum (but poor compared with Tune A) momentum selection and transmission for B1. This solution would seem to have no better transmission for B5 than Tune A, so it has little going for it.

Note: B and C are not ideal for the B1 line! Tune A has been found to give more transmission (x1.5 to 2) and a smaller spot at B' than the previous E766 tune.

Tune A

June 5, 1985

Q1-5 are set for 10 GeV B1 running.



Dibble	pol.	current	kg/inch
950	A	.950 kA	1.094
1043	B	.652	-.835
2560	A	1.60 kA	6.825
2976	B	-1.86	-7.855

Tune B

3" quads

3



kg/inch

2.489

-2.3

A 2.17kA

B -1.80kA

÷.625 to get dibbuk cts.

1.70kA

-2.45kA

A

B

Tune C

(4)



2.5
2.0
1.5
1.0
0.5
0.0
0
10
20
30
40
50
60
EXP. 766, B5 LINE 5/24/85
Q1-3
Q4-5
D1
D2
D3
D4
5.88
-7.16
Q6
Q7
B' tgt
B tgt
kg/inch
-2.73
1.88
B -2.38kA
A 1.47kA
A 1.37kA
B -1.69kA

REVERSED Q1-5, 10.69 GEV TUNE FOR B1 **Tune D** 11-Jun-85 09:28



EXP. 766, B5 LINE 5/24/85

Dibbuk	pd.	current	kg/inch
920	B	920 amps	-1.056
899	A	562	719.
2464	A	1540	6.726
3019	B	1887	-7.855

Tune A June 5, 1985

"EXP. 766, B5 LINE 5/24/85

DRIFT	3.	"D1	5.69000	0.00000	0.00000	0.00000
QUAD*	5.	"Q1	0.93200	1.09400	2.54000	23.83800
DRIFT	3.	"D2	0.24900	0.00000	0.00000	0.00000
QUAD*	5.	"Q2	0.93200	1.09400	2.54000	23.83800
DRIFT	3.	"L2	0.24900	0.00000	0.00000	0.00000
QUAD*	5.	"Q3	0.93200	1.09400	2.54000	23.83800
DRIFT	3.	"L3	0.43500	0.00000	0.00000	0.00000
QUAD*	5.	"Q4	1.32100	-0.83500	2.54000	-21.67200
DRIFT	3.	"L4	0.25300	0.00000	0.00000	0.00000
QUAD*	5.	"Q5	1.32100	-0.83500	2.54000	-21.67200
DRIFT	3.	"L5	5.48000	0.00000	0.00000	0.00000
ROTAT	2.		0.60000	0.00000	0.00000	0.00000
BEND*	4.	"D1	1.98100	9.88300	0.00000	1.17900
ROTAT	2.		0.60000	0.00000	0.00000	0.00000
DRIFT	3.		0.50800	0.00000	0.00000	0.00000
ROTAT	2.		0.60000	0.00000	0.00000	0.00000
BEND*	4.	"D2	1.98100	9.88300	0.00000	1.17900
ROTAT	2.		0.60000	0.00000	0.00000	0.00000
DRIFT	3.		2.35000	0.00000	0.00000	0.00000
BEND*	4.	"D3	1.98100	0.00000	0.00000	0.00000
DRIFT	3.		11.96000	0.00000	0.00000	0.00000
BEND*	4.	"D4	1.07000	0.00000	0.00000	0.00000
DRIFT	3.		0.50000	0.00000	0.00000	0.00000
QUAD*	5.0 1	"Q6	1.00000	6.82500	2.54000	3.70900
DRIFT	3.		0.91000	0.00000	0.00000	0.00000
QUAD*	5.0 1	"Q7	1.00000	-7.85500	2.54000	-2.91300
DRIFT	3.		8.43000	0.00000	0.00000	0.00000
FIT	10.		1.00010	0.10000	0.01000	0.11500
FIT	10.		3.00030	0.10000	0.01000	0.10390
	0.		0.00000	0.00000	0.00000	0.00000

Tune B

DRIFT	3.	"D1	5.69000	0.00000	0.00000	0.00000
QUAD*	5.	"Q1	0.93200	2.48900	2.54000	10.56600
DRIFT	3.	"D2	0.24900	0.00000	0.00000	0.00000
QUAD*	5.	"Q2	0.93200	2.48900	2.54000	10.56600
DRIFT	3.	"L2	0.24900	0.00000	0.00000	0.00000
QUAD*	5.	"Q3	0.93200	2.48900	2.54000	10.56600
DRIFT	3.	"L3	0.43500	0.00000	0.00000	0.00000
QUAD*	5.	"Q4	1.32100	-2.10100	2.54000	-8.48300
DRIFT	3.	"L4	0.25300	0.00000	0.00000	0.00000
QUAD*	5.	"Q5	1.32100	-2.54900	2.54000	-6.95500
DRIFT	3.	"L5	5.48000	0.00000	0.00000	0.00000
ROTAT	2.		0.60000	0.00000	0.00000	0.00000
BEND*	4.	"D1	1.98100	9.88300	0.00000	1.17900
ROTAT	2.		0.60000	0.00000	0.00000	0.00000
DRIFT	3.		0.50800	0.00000	0.00000	0.00000
ROTAT	2.		0.60000	0.00000	0.00000	0.00000
BEND*	4.	"D2	1.98100	9.88300	0.00000	1.17900
ROTAT	2.		0.60000	0.00000	0.00000	0.00000
DRIFT	3.		2.35000	0.00000	0.00000	0.00000
BEND*	4.	"D3	1.98100	0.00000	0.00000	0.00000
DRIFT	3.		11.96000	0.00000	0.00000	0.00000
BEND*	4.	"D4	1.07000	0.00000	0.00000	0.00000
DRIFT	3.		0.50000	0.00000	0.00000	0.00000
QUAD*	5.0 1	"Q6	1.00000	7.21500	2.54000	3.51900
DRIFT	3.		0.91000	0.00000	0.00000	0.00000
QUAD*	5.0 1	"Q7	1.00000	-8.81900	2.54000	-2.57800
DRIFT	3.		8.43000	0.00000	0.00000	0.00000
FIT	10.		1.00010	0.10000	0.01000	0.15080
FIT	10.		3.00030	0.10000	0.01000	0.12700
	0.		0.00000	0.00000	0.00000	0.00000

Tune C

"EXP. 766, B5 LINE 5/24/85

DRIFT	3.	"D1	5.69000	0.00000	0.00000	0.00000
QUAD*	5.	"Q1	0.93200	-2.73300	2.54000	-9.32600
DRIFT	3.	"D2	0.24900	0.00000	0.00000	0.00000
QUAD*	5.	"Q2	0.93200	-2.73300	2.54000	-9.32600
DRIFT	3.	"L2	0.24900	0.00000	0.00000	0.00000
QUAD*	5.	"Q3	0.93200	-2.73300	2.54000	-9.32600
DRIFT	3.	"L3	0.43500	0.00000	0.00000	0.00000
QUAD*	5.	"Q4	1.32100	1.88400	2.54000	9.92500
DRIFT	3.	"L4	0.25300	0.00000	0.00000	0.00000
QUAD*	5.	"Q5	1.32100	1.88400	2.54000	9.92500
DRIFT	3.	"L5	5.48000	0.00000	0.00000	0.00000
ROTAT	2.		0.60000	0.00000	0.00000	0.00000
BEND*	4.	"D1	1.98100	9.88300	0.00000	1.17900
ROTAT	2.		0.60000	0.00000	0.00000	0.00000
DRIFT	3.		0.50800	0.00000	0.00000	0.00000
ROTAT	2.		0.60000	0.00000	0.00000	0.00000
BEND*	4.	"D2	1.98100	9.88300	0.00000	1.17900
ROTAT	2.		0.60000	0.00000	0.00000	0.00000
DRIFT	3.		2.35000	0.00000	0.00000	0.00000
BEND*	4.	"D3	1.98100	0.00000	0.00000	0.00000
DRIFT	3.		11.96000	0.00000	0.00000	0.00000
BEND*	4.	"D4	1.07000	0.00000	0.00000	0.00000
DRIFT	3.		0.50000	0.00000	0.00000	0.00000
QUAD*	5.0 1	"Q6	1.00000	5.88300	2.54000	4.27500
DRIFT	3.		0.91000	0.00000	0.00000	0.00000
QUAD*	5.0 1	"Q7	1.00000	-7.16300	2.54000	-3.20900
DRIFT	3.		8.43000	0.00000	0.00000	0.00000
FIT	10.		1.00010	0.10000	0.01000	0.22700
FIT	10.		3.00030	0.10000	0.01000	

TUNE D

"EXP: 7L3, B5 LINE 5/24/85

DRIFT	3.	"D1	5.69000	0.00000	0.00000	0.00000
QUAD*	5.	"Q1	0.93200	-1.05600	2.54000	-24.37900
DRIFT	3.	"D2	0.24900	0.00000	0.00000	0.00000
QUAD*	5.	"Q2	0.93200	-1.05600	2.54000	-24.37900
DRIFT	3.	"L2	0.24900	0.00000	0.00000	0.00000
QUAD*	5.	"Q3	0.93200	-1.05600	2.54000	-24.37900
DRIFT	3.	"L3	0.43500	0.00000	0.00000	0.00000
QUAD*	5.	"Q4	1.32100	0.71900	2.54000	25.64400
DRIFT	3.	"L4	0.25300	0.00000	0.00000	0.00000
QUAD*	5.	"Q5	1.32100	0.71900	2.54000	25.64400
DRIFT	3.	"L5	5.48000	0.00000	0.00000	0.00000
ROTAT	2.		0.60000	0.00000	0.00000	0.00000
BEND*	4.	"D1	1.98100	9.88300	0.00000	1.17900
ROTAT	2.		0.60000	0.00000	0.00000	0.00000
DRIFT	3.		0.50800	0.00000	0.00000	0.00000
ROTAT	2.		0.60000	0.00000	0.00000	0.00000
BEND*	4.	"D2	1.98100	9.88300	0.00000	1.17900
ROTAT	2.		0.60000	0.00000	0.00000	0.00000
DRIFT	3.		2.35000	0.00000	0.00000	0.00000
BEND*	4.	"D3	1.98100	0.00000	0.00000	0.00000
DRIFT	3.		11.96000	0.00000	0.00000	0.00000
BEND*	4.	"D4	1.07000	0.00000	0.00000	0.00000
DRIFT	3.		0.50000	0.00000	0.00000	0.00000
QUAD*	5.0 1	"Q6	1.00000	6.72200	2.54000	3.76400
DRIFT	3.		0.91000	0.00000	0.00000	0.00000
QUAD*	5.0 1	"Q7	1.00000	-7.85500	2.54000	-2.91300
DRIFT	3.		8.43000	0.00000	0.00000	0.00000
FIT	10.		1.00010	0.10000	0.01000	0.12530
FIT	10.		3.00030	0.10000	0.01000	0.10030
	0.		0.00000	0.00000	0.00000	0.00000

B5 Q1-3 N8Q32



B5 Q1-3 N8Q52


36.7
36.6
36.5
36.4
36.3
36.2
36.1
36.0
35.9
35.8
35.7
35.6
35.5
D [IN]
0
0.4
0.8
1.2
1.6
2.0
2.4
2.8
3.2
I [KA]
10 X 10 TO THE CENTIMETER 46 1510
10 X 25 CM
KEUFFEL & ESSER CO.

A.D. GTD-2

Danby

B5 Q4-5

Multiply by kamps to get gradient



Fig. 6. Gradient, G point, vs I for 8 inch quadrupoles.

A.D. GTD-2
Danby

B5 Q4-5



Fig. 7. Magnet length, L_B, vs I for 8 inch quadrupoles. ($L_B = \Delta L_B + L_{core}$).


B5Q6/7
N3Q36-1
GAP
3" x 36"
H. x D.
Multiply by kamps to get gradient x length at a 1" radius.
ABSOLUTE ACCURACY ~2%
G(KG)/I(KA) x Lb (IN)
174.
170.
166.
162.
158.
154.
150.
146.
142.
138.
134.
130.
126.
0.4
0.8
1.2
1.6
2.0
2.4
2.8
3.2
I(KA)

B5D1

A. D. GTD-2

Danby



Fig. 2. $\int B_s ds$ vs I for 18D72 magnets.



Fig. 3. Magnet length, L_B, vs I for 18D72 magnets.



$(\sin\theta_f - \sin\theta_i)\, f\, [\text{Bev}/c] = \frac{1}{1313.22}\int B(s)\, ds\, [\text{KG-IN}]$
$= \frac{BL_B}{1313.22}\, [\text{KG-IN}]$
746.0
742.0
738.0
734.0
730.0
726.0
722.0
$\frac{BL_B}{I}\left[\frac{\text{KG-IN}}{\text{KA}}\right]$
1×10^{-3}

B5D2

B5D2



I [KA]
0.4
0.6
0.8
1.0
1.2
1.4
1.6
1.8
2.0
718.0
714.0
710.0
706.0
702.0
698.0
694.0
× 400 → 2400 A
⊙ 2400 → 400 A
30D72
K+E 10 X 10 TO THE CM. 359-14L
KEUFFEL & ESSER CO.



RUN PLTR

ENTER UP TO 55 CHARACTERS OF DESCRIPTION:

"EXP. 766, B5 LINE 5/24/85

(2)

DRIFT	3.	"D1	5.69000	0.00000	0.00000	0.00000
QUAD*	5.	"Q1	0.93200	1.09400	2.54000	23.83800
DRIFT	3.	"D2	0.24900	0.00000	0.00000	0.00000
QUAD*	5.	"Q2	0.93200	1.09400	2.54000	23.83800
DRIFT	3.	"L2	0.24900	0.00000	0.00000	0.00000
QUAD*	5.	"Q3	0.93200	1.09400	2.54000	23.83800
DRIFT	3.	"L3	0.43500	0.00000	0.00000	0.00000
QUAD*	5.	"Q4	1.32100	-1.34000	2.54000	-13.42300
DRIFT	3.	"L4	0.25300	0.00000	0.00000	0.00000
QUAD*	5.	"Q5	1.32100	-1.34000	2.54000	-13.42300
DRIFT	3.	"L5	5.48000	0.00000	0.00000	0.00000
ROTAT	2.		0.60000	0.00000	0.00000	0.00000
BEND*	4.	"D1	1.98100	9.88300	0.00000	1.17900
ROTAT	2.		0.60000	0.00000	0.00000	0.00000
DRIFT	3.		0.50800	0.00000	0.00000	0.00000
ROTAT	2.		0.60000	0.00000	0.00000	0.00000
BEND*	4.	"D2	1.98100	9.88300	0.00000	1.17900
ROTAT	2.		0.60000	0.00000	0.00000	0.00000
DRIFT	3.		2.35000	0.00000	0.00000	0.00000
BEND*	4.	"D3	1.98100	0.00000	0.00000	0.00000
DRIFT	3.		11.96000	0.00000	0.00000	0.00000
BEND*	4.	"D4	1.07000	0.00000	0.00000	0.00000
DRIFT	3.		0.50000	0.00000	0.00000	0.00000
QUAD*	5.0 1	"Q6	1.00000	6.81700	2.54000	3.71400
DRIFT	3.		0.91000	0.00000	0.00000	0.00000
QUAD*	5.0 1	"Q7	1.00000	-7.63000	2.54000	-3.00300
DRIFT	3.		8.43000	0.00000	0.00000	0.00000
FIT	10.		1.00010	0.10000	0.01000	0.10030
FIT	10.		3.00030	0.10000	0.01000	0.10630

RUN PLTR

ENTER UP TO 55 CHARACTERS OF DESCRIPTION:

3" quads
//cc

3

LE7762.W




```
5.01 1.0 6. 2.54 'Q6' ;
.^C$$
```

→ : requested sizes

```
.TECO FOR05.DAT4HARACTERS OF DESCRIPTION:

[2K Core]
*SQ4$0LT$$
5.0 1.321 -1.395 2.54 'Q4' ;
*FS1.395$2.101$EX$$
CPU TIME: 4.36  ELAPSED TIME: 6.63
.TY FOR05.DAT
 'EXP. 766, B5 LINE 5/24/85'
0RUN PLTR
1.    .13    1.    .13    2.    0.    .3    28.5   ;
16.    3.    1836.15   ;
3.0    5.69    'D1'   *CTERS OF DESCRIPTION:
5.0    .932 2.489 2.54 'Q1' ;
3.0    .249    'D2'    *
5.0 .932 2.489 2.54 'Q2' ;
3.0    .249    'L2'    *
```

```
DRIFT   3.        "D1      5.69000    0.00000    0.00000    0.00000
QUAD*   5.        "Q1      0.93200    2.48900    2.54000   10.56600
DRIFT   3.        "D2      0.24900    0.00000    0.00000    0.00000
QUAD*   5.        "Q2      0.93200    2.48900    2.54000   10.56600
DRIFT   3.        "L2      0.24900    0.00000    0.00000    0.00000
QUAD*   5.        "Q3      0.93200    2.48900    2.54000   10.56600
DRIFT   3.        "L3      0.43500    0.00000    0.00000    0.00000
QUAD*   5.        "Q4      1.32100   -2.10100    2.54000   -8.48300
DRIFT   3.        "L4      0.25300    0.00000    0.00000    0.00000
QUAD*   5.        "Q5      1.32100   -2.54900    2.54000   -6.95500
DRIFT   3.        "L5      5.48000    0.00000    0.00000    0.00000
ROTAT   2.                 0.60000    0.00000    0.00000    0.00000
BEND*   4.        "D1      1.98100    9.88300    0.00000    1.17900
ROTAT   2.                 0.60000    0.00000    0.00000    0.00000
DRIFT   3.                 0.50800    0.00000    0.00000    0.00000
ROTAT   2.                 0.60000    0.00000    0.00000    0.00000
BEND*   4.        "D2      1.98100    9.88300    0.00000    1.17900
ROTAT   2.                 0.60000    0.00000    0.00000    0.00000
DRIFT   3.                 2.35000    0.00000    0.00000    0.00000
BEND*   4.        "D3      1.98100    0.00000    0.00000    0.00000
DRIFT   3.                11.96000    0.00000    0.00000    0.00000
BEND*   4.        "D4      1.07000    0.00000    0.00000    0.00000
DRIFT   3.                 0.50000    0.00000    0.00000    0.00000
QUAD*   5.0 1     "Q6      1.00000    7.21500    2.54000    3.51900
DRIFT   3.                 0.91000    0.00000    0.00000    0.00000
QUAD*   5.0 1     "Q7      1.00000   -8.81900    2.54000   -2.57800
DRIFT   3.                 8.43000    0.00000    0.00000    0.00000
FIT    10.                 1.00010    0.10000    0.01000    0.15080
FIT    10.                 3.00030    0.10000    0.01000    0.12700
        0.                 0.00000    0.00000    0.00000    0.00000

5.01 1.0 6. 2.54 'Q6' ;
.^C$$

.TECO FOR05.DAT4HARACTERS OF DESCRIPTION:

[2K Core]
*SQ4$0LT$$
5.0 1.321 -1.395 2.54 'Q4' ;
*FS1.395$2.101$EX$$
CPU TIME: 4.36  ELAPSED TIME: 6.63
.TY FOR05.DAT
 'EXP. 766, B5 LINE 5/24/85'
0RUN PLTR
1.    .13    1.    .13    2.    0.    .3    28.5  ;
16.    3.    1836.15  ;
3.0    5.69    'D1'   *CTERS OF DESCRIPTION:
5.0    .932 2.489 2.54 'Q1' ;
3.0    .249    'D2'    *
5.0 .932 2.489 2.54 'Q2' ;
3.0    .249    'L2'    *
5.0 .932 2.489 2.54 'Q3' ;
```

(4)

E7763.dat




```
*S884$I $0TT$$
5.0 1.321 1.884 2.54 'Q4' ;
*S10. $0LT$$
10. 1. 1. 2. .1 ;ARACTERS OF DESCRIPTION:
*4K$EX$$

.RUN TT\T\RANS[25,64

STOP

END OF EXECUTION
CPU TIME: 3.88  ELAPSED TIME: 12.13
EXIT

.RUN PLTR

ENTER UP TO 55 CHARACTERS OF DESCRIPTION:
```

Q1-3 } reversed polarity
Q4-5

"EXP. 766, B5 LINE 5/24/85

DRIFT	3.	"D1	5.69000	0.00000	0.00000	0.00000
QUAD*	5.	"Q1	0.93200	-2.73300	2.54000	-9.32600
DRIFT	3.	"D2	0.24900	0.00000	0.00000	0.00000
QUAD*	5.	"Q2	0.93200	-2.73300	2.54000	-9.32600
DRIFT	3.	"L2	0.24900	0.00000	0.00000	0.00000
QUAD*	5.	"Q3	0.93200	-2.73300	2.54000	-9.32600
DRIFT	3.	"L3	0.43500	0.00000	0.00000	0.00000
QUAD*	5.	"Q4	1.32100	1.88400	2.54000	9.92500
DRIFT	3.	"L4	0.25300	0.00000	0.00000	0.00000
QUAD*	5.	"Q5	1.32100	1.88400	2.54000	9.92500
DRIFT	3.	"L5	5.48000	0.00000	0.00000	0.00000
ROTAT	2.		0.60000	0.00000	0.00000	0.00000
BEND*	4.	"D1	1.98100	9.88300	0.00000	1.17900
ROTAT	2.		0.60000	0.00000	0.00000	0.00000
DRIFT	3.		0.50800	0.00000	0.00000	0.00000
ROTAT	2.		0.60000	0.00000	0.00000	0.00000
BEND*	4.	"D2	1.98100	9.88300	0.00000	1.17900
ROTAT	2.		0.60000	0.00000	0.00000	0.00000
DRIFT	3.		2.35000	0.00000	0.00000	0.00000
BEND*	4.	"D3	1.98100	0.00000	0.00000	0.00000
DRIFT	3.		11.96000	0.00000	0.00000	0.00000
BEND*	4.	"D4	1.07000	0.00000	0.00000	0.00000
DRIFT	3.		0.50000	0.00000	0.00000	0.00000
QUAD*	5.0 1	"Q6	1.00000	5.88300	2.54000	4.27500
DRIFT	3.		0.91000	0.00000	0.00000	0.00000
QUAD*	5.0 1	"Q7	1.00000	-7.16300	2.54000	-3.20900
DRIFT	3.		8.43000	0.00000	0.00000	0.00000
FIT	10.		1.00010	0.10000	0.01000	0.22700
FIT	10.		3.00030	0.10000	0.01000	

```
*S884$I $0TT$$
5.0 1.321 1.884 2.54 'Q4' ;
*S10. $0LT$$
10. 1. 1. 2. .1 ;ARACTERS OF DESCRIPTION:
*4K$EX$$

.RUN TT\T\RANS[25,64


STOP

END OF EXECUTION
CPU TIME: 3.88  ELAPSED TIME: 12.13
EXIT

.RUN PLTR


ENTER UP TO 55 CHARACTERS OF DESCRIPTION:
```